



GEER ELECTRONICSTECHNOLOGYCO.,LTD

Products Specification For Approval

Manufacturer	GEER ELECTRONICSTECHNOLOGY CO.,LTD
Product Name	Ufos type mining lamp of power supply
Product Number	
Product Specification	GH-UFO-FJC150W-PC
Customer	
CUST PT/NO.	UFO-150W-102V-PC
REV	V1.0

Supplier Singnature	Customer Singnature
Prepared By	Tested By
Checked By	Checked By
Approved By	Approved By
Supplier	Customer
Date	Date



GEER ELECTRONICSTECHNOLOGYCO.,LTD

■ Product features:

.International universal voltage ac input (176-265VAC);

- ·Built-in active single pole PFC function circuit;
- ·Product protection type: short circuit; Open road, overload;
- ·Heat dissipation: natural air cooling;
- · Product protection grade: IP65, indoor and outdoor can be installed;
- ·Suitable for LED mining lamp; floodlight; project lamp; ceiling lamp drive installation;
- ·It can be used in a dry, wet, rain-soaked environment;
- .Input Surge Protection: 3kV line-line;
- 3 years warranty (ambient temperature is highest do not exceed 45°C)


■ Electrical specifications:


Product model		GH-UFO-FJC150W-PC	
Output	Output voltage	120-135V (Wave) no-load	
character istic	Output current	1380mA +/- 5%	
	Constant current	90-110VDC	
	range		
	Rated power	140W-160W (MAX Input power:160W)	
	THD	≤15%	
Input	Input voltage range	176-265VAC	
character istic	Frequency range	50-60Hz	
	Input current	≤0.95A	
	Power factor	PF≥0. 95	
	Efficiency	≥92%	
Operating	Operating temperature	-30° C45° C	
environme nt	Operating humidity	20-95%RH, Non-condensing	
	Storage temperature	-4080° C	
	Storage humidity	10-95%RH	
Function	Short circuit protection: the output can be short-circuited for a long time when the product is normal;		
protection	ion Remove short circuit, product recovery normal output;		
	Open circuit: the output can be open for a long time when the product is in normal power;		
Withstand	voltage	II/P-FG 1.5KVAC O/P-FG 1.5KVAC	
Other Boundary dimension		φ 150x72mm; pitch of positioning: φ 133mm	
Qı	uality guarantee	3 years warranty;	
Packaging Pa		Paper box add Pearl cushion; A single packaging	



GEER ELECTRONICSTECHNOLOGYCO.,LTD

■ Boundary dimension :





Input Cable: protect wire of black rubber, OD: Φ7.2mm, 3 x 1mm2, protruded lengths: 350mm Output Cable: protect wire of black rubber, OD: Φ7.2mm, 2 x 1mm2, protruded lengths: 240mm

■ The product labeling:

